hpack Documentation

Release 2.0.1

Cory Benfield

Aug 30, 2020

Contents

1 Contents **3**
1.1 Installing hpack 3
1.2 hpack API 3

Index **5**

hpack provides a simple Python interface to the HPACK compression algorithm, used to compress HTTP headers in HTTP/2. Used by some of the most popular HTTP/2 implementations in Python, HPACK offers a great Python interface as well as optional upgrade to optimised C-based compression routines from nghttp2.

Using hpack is easy:

```
from hpack import Encoder, Decoder

e = Encoder()
encoded_bytes = e.encode(headers)

d = Decoder()
decoded_headers = d.decode(encoded_bytes)
```

hpack will transparently use nghttp2 on CPython if it's available, gaining even better compression efficiency and speed, but it also makes available a pure-Python implementation that conforms strictly to RFC 7541.

CHAPTER 1

Contents

1.1 Installing hpack

hpack is trivial to install from the Python Package Index. Simply run:

```
$ pip install hpack
```

Alternatively, feel free to download one of the release tarballs from our GitHub page, extract it to your favourite directory, and then run

```
$ python setup.py install
```

hpack has no external dependencies.

1.1.1 Using nghttp2

If you want to use nghttp2 with hpack, all you need to do is install it along with its Python bindings. Consult nghttp2's documentation for instructions on how to install it.

1.2 hpack API

This document provides the HPACK API.

class hpack.**Encoder**

An HPACK encoder object. This object takes HTTP headers and emits encoded HTTP/2 header blocks.

encode(*headers*, *huffman=True*)

Takes a set of headers and encodes them into a HPACK-encoded header block.

Parameters

- **headers** – The headers to encode. Must be either an iterable of tuples or a `dict`.

  If an iterable of tuples, the tuples may be either two-tuples or three-tuples. If they are two-tuples, the tuples must be of the format `(name, value)`. If they are three-tuples, they must be of the format `(name, value, sensitive)`, where `sensitive` is a boolean value indicating whether the header should be added to header tables anywhere. If not present, `sensitive` defaults to `False`.

- **huffman** – (optional) Whether to Huffman-encode any header sent as a literal value. Except for use when debugging, it is recommended that this be left enabled.

Returns A bytestring containing the HPACK-encoded header block.

header_table_size
Controls the size of the HPACK header table.

class hpack.**Decoder**
An HPACK decoder object.

decode(*data*)
Takes an HPACK-encoded header block and decodes it into a header set.

Parameters **data** – A bytestring representing a complete HPACK-encoded header block.

Returns A list of two-tuples of `(name, value)` representing the HPACK-encoded headers, in the order they were decoded.

Raises ***HPACKDecodingError*** – If an error is encountered while decoding the header block.

header_table_size
Controls the size of the HPACK header table.

class hpack.**HPACKError**
The base class for all `hpack` exceptions.

class hpack.**HPACKDecodingError**
An error has been encountered while performing HPACK decoding.

Index

D

decode() (*hpack.Decoder method*), 4
Decoder (*class in hpack*), 4

E

encode() (*hpack.Encoder method*), 3
Encoder (*class in hpack*), 3

H

header_table_size (*hpack.Decoder attribute*), 4
header_table_size (*hpack.Encoder attribute*), 4
HPACKDecodingError (*class in hpack*), 4
HPACKError (*class in hpack*), 4